

Thank you for choosing **KennelMaster** black chain link kennel. We aim to assist you in your assembly of this new, safe containment space for your pet. You will need the following tools:

- Hammer
- Screw gun with Philips drive
- Adjustable wrench
- Pliers
- Tape measure

Let's get started!

- Select a flat, shaded location for the kennel placement.
- Begin by laying out and assembling the top and bottom frame.
- Plan layout and gate placement by inserting a hinge post at the desired gate position.
- The gate may go on either side of the hinge post. Take a moment, be sure to place the tension strip so the hooks will be facing the proper direction to receive the chain link fabric.
- Insert remaining five vertical posts into bottom frame and add the already built top frame, taking care to line the frame up with the six vertical posts.
- Next, install the gate by dropping gate hinge pins into the gate post hinges, then securing them with hitch pins.
- Assemble two corrugated jacks. (these are optional, they are used to lift the kennel up if needed)
- Raise the kennel off the ground and place it on the corrugated jacks.
- Install the latch post with 20 inches between posts for the gate.
- Check the gate and latch operation by swinging the gate and engaging latch.
- Place one self-drilling screw through the top and bottom of the gatepost to secure.
- Repeat process on the remaining vertical posts.
- Add chain link using two people. Attach the chain link fabric to the tension strip.
- Primp the hooks on the tension strip closed to secure.
- Then unroll the chain link as you wrap it around the frame.
- Stretch the remainder of the chain link roll around the kennel.
- Tighten the fabric by taking the slack out of it on each side, pulling and stretching the fabric, working it around each section of the kennel.
- If the fabric needs to be shortened to achieve desired tension, unlock top and bottom knuckles, then twist the wire up and out.
- Remove these wires in pairs to retain alignment with the tension strip.
- Once it is attached to the tension strip, rip the hooks with pliers.
- Wrap the spooled wire end around the screw at the top corner of the gate frame.
- Tighten the screw with a screw gun.
- Secure chain link fabric to the top frame by looping wire around the frame and through the chain link fabric at every other diamond, pulling the wire tight as you want.
- Pull the wire tight and secure the end of the wire to the frame screw.
- Secure tie the bottom.
- Raise the kennel off the ground.
- Place it on all four corrugated jacks.
- Repeat the secure tie process around bottom perimeter.
- This time, tie through each diamond, pulling the wire tight as you want.

- Tying through every diamond helps prevent your pet from escaping from the enclosure.
- Install each of the six feet by pushing each foot onto the frame.

Install shade roof: Stretch the roofing cloth across the top of the kennel and secure loosely with zip ties. Once you have adjusted the fabric to proper fit, tighten all the zip ties.

For the final step, secure the kennel to the ground with ground anchors. Push clamps around frame to place stakes through holes and hammer them into the ground at an angle.

Congratulations on creating a secure enclosure for your pet!